

**Product:** Deuterium  
**UN No:** 1957

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

Product identifier : Deuterium  
Chemical formula : D<sub>2</sub>  
Synonyms : Normal Deuterium, Heavy Hydrogen, Deuterium

Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : General Industrial  
Restrictions on use : No data available

Details of the Supplier : CK Special Gases Ltd  
Ashby Suite, Wellington House  
Leicester Road, Ibstock  
Leicestershire  
LE67 6HP

Email Address : sales@ckgas.com

Telephone : +44(0)1530 267209  
Emergency Telephone (24 hours) : Web Version

---

## 2. HAZARDS IDENTIFICATION

Classification according to Regulation 1272/2008 (CLP)  
Flammable gases – Category 1 H220 : Extremely flammable gas.  
Gases under pressure - Compressed gas. H280:Contains gas under pressure; may explode if heated.

Label Elements according to Regulation 1272/2008 (CLP)

Hazard pictograms/symbols



Signal Word : Danger

Hazard Statements : H220:Extremely flammable gas.  
H280:Contains gas under pressure; may explode if heated.

# SAFETY DATA SHEET

MSDS No: CKSG-01-1957

**Product: Deuterium**
**UN No: 1957**

Precautionary Statements :

 Prevention : P210:Keep away from heat/sparks/open flame/hot surfaces.  
No smoking.

 Response : P377:Leaking gas fire : Do not extinguish, unless leak can be stopped safely.  
P381:Eliminate all ignition sources if safe to do so.

 Storage : P403:Store in a well-ventilated place.  
P410:Protect from sunlight.

## Classification (Directive)

F+ Extremely flammable.

R12 Extremely flammable.

## Other Hazards

High pressure gas.

Can cause rapid suffocation.

Extremely flammable.

May form explosive mixtures in air.

Immediate fire and explosion hazard exists when mixed with air at concentrations exceeding the lower flammability limit (LFL).

High concentrations that can cause rapid suffocation are within the flammable range and should not be entered.

Avoid breathing gas.

Self contained breathing apparatus (SCBA) may be required.

## Environmental Effects

Not harmful.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Mixture :

Substance

Components	EINECS / ELINCS Number	CAS Number	Concentration (Volume)
Deuterium	231-952-7	7782-39-0	100 %

Components	Classification (Directive)	Classification (CLP)	REACH Reg. #
Deuterium	F+ R12	Flam. Gas 1 Press. Gas	

**Product: Deuterium**  
**UN No: 1957**

If REACH registration numbers do not appear the substance is either exempt from registration, does not meet the minimum volume threshold for registration, or the registration date has not yet come due. Refer to section 16 for full text of each relevant R-phrases and H-phrases.

Concentration is nominal. For the exact product composition, please refer to CK Special Gases technical specifications.

---

## **4. FIRST AID MEASURES**

### Description of first aid measures

General advice :	Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Skin contact :	Not applicable.
Ingestion :	Ingestion is not considered a potential route of exposure.
Inhalation :	In case of shortness of breath, give oxygen. Remove to fresh air. If breathing has stopped or is laboured, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Seek medical advice.

### Most important symptoms and effects, both acute and delayed

Symptoms :	Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.
------------	----------------------------------------------------------------------------------------------------------------------------------------------------

Indication of any immediate medical attention and special treatment needed  
No data available.

---

## **5. FIRE-FIGHTING MEASURES**

### Extinguishing media

Suitable extinguishing media :	All known extinguishing media can be used.
--------------------------------	--------------------------------------------

Extinguishing media which must not be used for safety reasons :	No data available.
-----------------------------------------------------------------	--------------------

**Product: Deuterium**

**UN No: 1957**

Special hazards arising from the substance or mixture :

Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Keep containers and surroundings cool with water spray. Extinguish fire only if gas flow can be stopped. If possible, shut off the source of gas and allow the fire to burn itself out. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Move away from container and cool with water from a protected position. Keep adjacent cylinders cool by spraying with large amounts of water until fire burns itself out. If flames are accidentally extinguished, explosive re-ignition may occur; therefore, appropriate measures should be taken (e.g. total evacuation to protect persons from cylinder fragments and toxic fumes should a rupture occur).

Advice for fire-fighters :

Wear self-contained breathing apparatus for fire fighting if necessary.

Further information :

No data available.

---

## **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective

equipment and emergency procedures : Evacuate personnel to safe areas. Remove all sources of ignition. Never enter a confined space or other area where the flammable gas concentration is greater than 10% of its lower flammable limited. Ventilate the area.

Environmental precautions :

Do not discharge into any place where its accumulation could be dangerous. Should not be released into the environment. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up :

Ventilate the area. Approach suspected leak areas with caution.

Additional advice :

Increase ventilation to the release area and monitor concentrations. If leak is from cylinder or cylinder valve, call the CK Special Gases emergency telephone number. If the leak is in the user's system, close the cylinder valve, safely vent the pressure, and purge with an inert gas before attempting repairs.

---

**Product: Deuterium****UN No: 1957****7. HANDLING AND STORAGE**

## Precautions for safe handling

Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122° F). Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Use an adjustable strap wrench to remove over-tight or rusted caps. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to occur. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Replace outlet caps or plugs and container caps as soon as container is disconnected from equipment. Do not subject containers to abnormal mechanical shocks which may cause damage to their valve or safety devices. Never attempt to lift a cylinder by its valve protection cap or guard. Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Do not smoke while handling product or cylinders. Never re-compress a gas or a gas mixture without first consulting the supplier. Never attempt to transfer gases from one cylinder/container to another. Always use backflow protective device in piping. Purge air from system before introducing gas. When returning cylinder install valve outlet cap or plug leak tight. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122°F). Prolonged periods of cold temperature below -30°C (-20°F ) should be avoided. Ensure equipment is adequately earthed.

## Conditions for safe storage, including any incompatibilities

Containers should be stored in a purpose built compound which should be well ventilated, preferably in the open air. Observe all regulations and local requirements regarding storage of containers. Stored containers should be periodically checked for general condition and leakage. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C (122°F). Smoking should be prohibited within storage areas or while handling product or containers. Display "No Smoking or Open Flames" signs in the storage areas. The amounts of flammable or toxic gases in storage should be kept to a minimum. Return empty containers in a timely manner.

**Product: Deuterium****UN No: 1957**

## Technical measures/Precautions

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations. Keep away from combustible material. All electrical equipment in the storage areas should be compatible with flammable materials stored. Containers containing flammable gases should be stored away from other combustible materials. Where necessary containers containing oxygen and oxidants should be separated from flammable gases by a fire resistant partition.

## Specific end use(s)

Refer to section 1 or the extended SDS if applicable

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

## Control parameters

If applicable, refer to the extended section of the SDS for further information on CSA.

## Exposure controls

## Engineering measures

Provide natural or explosion-proof ventilation that is adequate to ensure flammable gas does not reach its lower explosive limit.

## Personal protective equipment

Respiratory protection : High concentrations that can cause rapid suffocation are within flammable Range and should not be entered.

Hand protection : Sturdy work gloves are recommended for handling cylinders.  
The breakthrough time of the selected glove(s) must be greater than the intended use period.

Eye protection : Safety glasses recommended when handling cylinders.

Skin and body protection : Safety shoes are recommended when handling cylinders.

Wear as appropriate: flame retardant protective clothing.

Special instructions for protection and hygiene :

Ensure adequate ventilation, especially in confined areas.

**9. PHYSICAL**

## Information on basic physical and chemical properties

Appearance : Compressed gas. Colourless gas

Odour : None.

Odour threshold : No data available.

pH : Not applicable.

**Product: Deuterium****UN No: 1957**

Melting point/range :	-426 °F (-254.4 °C)
Boiling point/range :	-417 °F (-249.4 °C)
Flash point :	Not applicable.
Evaporation rate :	Not applicable.
Flammability (solid, gas) :	No data available.
Upper/lower explosion/flammability limit :	79.6%(V) / 6.6%(V)
Vapour pressure :	Not applicable.
Water solubility :	No data available.
Relative vapour density :	0.139 (air = 1).
Relative density :	0.16 (water = 1).
Partition coefficient (n-octanol/water) :	Not applicable.
Autoignition temperature :	560 °C.
Decomposition temperature :	No data available.
Viscosity :	Not applicable.
Explosive properties :	No data available.
Oxidizing properties :	No data available.
Molecular Weight :	4.03 g/mol
Density :	0.0002 g/cm <sup>3</sup> (0.012 lb/ft <sup>3</sup> ) at 21 °C ( 70 °F) Note: (as vapour)
Specific Volume :	5.9931 m <sup>3</sup> /kg (96.01 ft <sup>3</sup> /lb) at 21 °C ( 70 °F)
Upper flammability limit :	79.6%(V)
Lower flammability limit :	6.6%(V)

---

## **10. STABILITY AND REACTIVITY**

Reactivity :	Refer to possibility of hazardous reactions and/or incompatible materials sections.
Chemical Stability :	Stable under normal conditions.
Possibility of hazardous reactions :	No data available.
Conditions to avoid :	Heat, flames and sparks. May form explosive mixtures with air and oxidizing agents.
Incompatible materials :	Oxygen. Oxidizing agents.
Hazardous decomposition products :	Incomplete combustion may form carbon monoxide.

---

## **11. TOXICOLOGICAL INFORMATION**

Information on toxicological effects

Likely routes of exposure

Effects on Eye :	No data available.
Effects on Skin :	No adverse effect.

# SAFETY DATA SHEET

MSDS No: CKSG-01-1957

**Product: Deuterium****UN No: 1957**

Inhalation Effects : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.

Ingestion Effects : Ingestion is not considered a potential route of exposure.

Symptoms : Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

**Acute toxicity**

Acute Oral Toxicity : No data is available on the product itself.

Inhalation : ISO TC58 (1h) : Method : Estimated.

Acute Dermal Toxicity : No data is available on the product itself.

Skin corrosion/irritation : No data available.

Serious eye damage/eye irritation : No data available.

Sensitization. : No data available.

**Chronic toxicity or effects from long term exposures**

Carcinogenicity : No data available.

Reproductive toxicity : No data is available on the product itself.

Germ cell mutagenicity : No data is available on the product itself.

Specific target organ systemic toxicity (single exposure) : No data available.

Specific target organ systemic toxicity (repeated exposure) : No data available.

Aspiration hazard : No data available.

---

**12. ECOLOGICAL INFORMATION****Toxicity**

Aquatic toxicity : No data is available on the product itself.

Toxicity to other organisms : No data is available on the product itself.

Persistence and degradability : No data available.

Bioaccumulative potential : No data is available on the product itself.

Mobility in soil : No data available.

Results of PBT and vPvB assessment : If applicable, refer to the extended section of the SDS for further information on CSA.

Other adverse effects : This product has no known eco-toxicological effects.

---



**Product: Deuterium****UN No: 1957****13. DISPOSAL CONSIDERATIONS**

Waste treatment methods : Contact supplier if guidance is required. Return unused product in original cylinder to supplier. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

Contaminated packaging : Return cylinder to supplier.

---

**14. TRANSPORT INFORMATION****ADR**

UN/ID No. :	UN1957
Proper shipping name :	DEUTERIUM, COMPRESSED
Class or Division :	2
Tunnel Code :	(B/D)
Label(s) :	2.1
ADR/RID Hazard ID no. :	23

**IATA**

UN/ID No. :	UN1957
Proper shipping name :	Deuterium, compressed
Class or Division :	2.1
Label(s) :	2.1

**IMDG**

UN/ID No. :	UN1957
Proper shipping name :	DEUTERIUM, COMPRESSED
Class or Division :	2.1
Label(s) :	2.1

**RID**

UN/ID No. :	UN1957
Proper shipping name :	DEUTERIUM, COMPRESSED
Class or Division :	2
Label(s) :	2.1

**Further Information**

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact a CK Special Gases customer service representative.

**Product: Deuterium****UN No: 1957****15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.
Canada	DSL	Included on Inventory.
Australia	AICS	Not on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.
Japan	ENCS	Not on Inventory.

WGK Identification Number : Not water endangering.

Chemical Safety Assessment

Refer to extended SDS for CSA information

This product is either exempt from REACH, does not meet the minimum volume threshold for a CSA, or the CSA has not yet been completed.

---

**16. OTHER INFORMATION**

Ensure all national/local regulations are observed.

R-phrases – Components

R12 Extremely flammable

Hazard Statements: H220 Extremely flammable gas.

Prepared by : CK Special Gases Ltd

For additional information, please visit our website at [www.ckgas.com](http://www.ckgas.com)

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.